




Printed: Apr 12, 2011

s T2	X YLE	5 : A	







KEY FOR PLATING AND TAIL LENGTH AND TYPE													
Х	TERMINAL PLATING (NOTE 10)	DIM S	TERMINAL TYPE										
-0XX(LF)	30u"/. 76u Au OVER 50u"/1. 27u Ni	. 105/2. 67	RD										
-1XX(LF)	30u″/.76 GXT GOLD FLASH	. 105/2. 67	RD										
-2XX(LF)	30u"/. 76u Au OVER 50u"/1. 27u Ni	. 150/3. 81	RD										
-3XX(LF)	30u″/.76 GXT GOLD FLASH	. 150/3. 81	RD										
-4XX(LF)	30u"/. 76u Au OVER 50u"/1. 27u Ni	. 105/2. 67	SQ										
-5XX(LF)	30u″/.76 GXT GOLD FLASH	. 105/2. 67	SQ										
-6XX(LF)	30u"/. 76u Au OVER 50u"/1. 27u Ni	. 150/3. 81	SQ										
-7XX(LF)	30u″/.76 GXT GOLD FLASH	. 150/3. 81	SQ										
-8XX(LF)	15u"/. 38u Au DVER 50u"/1. 27u Ni	. 150/3. 81	SQ										
-9XX(LF)	15u"/. 38u Au OVER 50u"/1. 27u Ni	. 105/2. 67	SQ										

NOTES

- SAME PIN POSITION TOLERANCE APPLIES TO BOTH ENDS OF EACH TERMINAL.
- MOLDING MAT'L;30% GLASS-FILLED POLYESTER, FLAME RETARDANT PER UL 94-VO, COLOR;BLUE.
- 3. 1.º MAX DRAFT PERMISSIBLE ON ALL SURFACES.
- 4. 1.8 KILOGRAMS/4 POUNDS MIN. TERM. PULL-OUT FORCE.
- 5. TERMINAL MAT'L: PHOSPHOR BRONZE.
- A. PART NUMBERS HAVING AN 'R' FOLLOWING THE 8 DIGIT P/N (EXAMPLE 69155-010 R) HAVE A RETENTION FEATURE. LOCATION IS MANUFACTURER'S OPTION.
 - B. CONNECTORS WITH RETENTION AND ROUND PINS HAVE 15LB/6. 8KG MAX INSERTION AND . 25LB/. 11KG MIN RETENTION FORCE WHEN USED IN A . 035/. 89±. 003/. 08 DIA HOLE AND . 062/1.58 THICK PCB BOARD
 - C. CONNECTORS WITH RETENTION AND SQUARE PINS HAVE A 15LB/6 8KG MAX INSERTION AND A .5LB/.23KG MIN RETENTION WHEN USED IN A .040/1.02±.003/.08 DIA HOLE AND A . 062/1.58 THICK PCB BOARD.
- (7) DIMENSION "A" FOR -034 HAS A MAXIMUM SIZE OF 1. 990/50. 6
- 8. 69155-***LF IS JUST A LEAD FREE PRODUCT.
- 9. THE HOUSING OF XXXXX-XYYLF WILL WITHSTAND EXPOSUURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER PROCESS.
- 10. PLATING OPTION: MAYBE EITHER GOLD OR GXT PLATING AT MANUFACTURER'S OPTION
- 11. FOR 69155-150LF , THE TOLERANCE OF DIM " S " IS " -0. 10 , +0. 35 ".

mat	i'l. co	de						ices ui se spe	CUSTOMER					FÇ	<u>]],</u>								
ltr	ecn	no	dr	date				.XX±.01/.X±.3				COPY				7	y		www	.fcicon	nect.co	om	
М					lin	ear	.xx	(±.005	/.XX±.13		projection		1	title		C		1					
							.xxxx	±.0020	/.XXX	±.051	\oplus		_1		HEADER QUICKIE								
					and	gles		0°±2°			7	7	7	RIGHT ANGLE 4						⊦ W/	WALL		
					dr	١	.COR	I.CORNMAN 8/10/		0/90				uct fa		Q	UICK	ΊE		code	;		
					ene	gr	M.SMY	Κ	8/1	0/90			size	dwg	no					-	-		
					chi	r 🗔	M.SMY	Κ	8/1	8/10/90 8/10/90				١, ١	al 69155						sheet		
					app	od	M.SMY	Κ	8/1					A 69135 ₂						2 0	f		
she	et	revision																					
inde	index sheet																						

PDM: Rev:M

3 STATUS Released

:	+			
Ĺ	٤			
•	ž			
	>			
,	÷			
•	è			
	벟			
į	٥			
	ţ			
	÷			
•	È			
į	せ			
	٤			
į	Ξ	Ħ		
•	~	ᇤ		
	ě	ŧ		
į	Ħ	₫		
;	ŗ	۲		
;	۵	9		
	ĕ	O		
•		ت		
•	=	5		
	٩	4		
2	è	۰	_	
and a summer of the summer of	form whatever is not permitted without written authority from t	Property of FCI. Copyright FCI.	В	
	*	ě		
:	ŧ	δ		
=	Œ.	Œ		
	_			

		1 2				3	4
PRODUCT NO NOTE 6	POS	DIM A	DIM B	DIM C	STYLE		
69155-X02(LF)	2X5	. 78/19. 8	. 72/18. 3	. 400/10, 16	В		
-X10(LF)	2X5	. 78/19. 8	. 72/18. 3	. 400/10. 16	А		
-X14(LF)	2X7	. 98/24. 9	, 92/23, 4	. 600/15. 24	С		
-X16(LF)	2X8	1. 08/27. 9	1. 02/25. 9	. 700/17. 78	D		
-X20(LF)	2X10	1. 28/32. 5	1, 22/31, 0	. 900/22. 86	٨		
-X24(LF)	2X12	1. 48/37. 6	1. 42/36. 1	1. 100/27. 94			
-X26(LF)	2X13	1. 58/40. 1	1, 52/38, 6	1. 200/30. 48			
-X30(LF)	2X15	1. 78/45. 2	1. 72/43. 7	1. 400/35. 56			
-X34(LF)	2X17	1, 98/50, 3	1. 92/48. 8	1. 600/40. 64		NOTE 7	
-X40(LF)	2X20	2, 28/57, 9	2, 22/56, 4	1. 900/48. 26			
-X44(LF)	2X22	2, 48/63, 0	2. 42/61. 5	2. 100/53. 34			
-X50(LF)	2X25	2, 78/70, 6	2, 72/69, 1	2. 400/60. 96	V	NOTE 11	
69155-X60(LF)	2X30	3, 28/83, 3	3, 22/81, 8	2. 900/73. 66	D		
						•	

mat'l. code						tolerances unless otherwise specified							CUSTOMER				FÇ						
ltr	ecn r	10	dr	date	•			.XX:	±.01/	′.X±.	3	COPY					=	IJ		www	.fcicon	nect.co	mc
М						linea	r 🗔	.XXX±.005/			.13	proje	projection tit				0.00		<i>/</i>	CLIN	4 11		
							.x:	.XXXX±.0020/.		′.XXX±.051		4	\bigoplus			HEADER QUICKIE SLIM RIGHT ANGLE 4 WA							ΝE
						angle	es	0°±2°				I W WI			h	RIGH	ΙA	NGL	<u> </u>	1 W	ALL		
						dr	M.C	.CORNMAN		8/1	0/90	INCH/MM		produ			Q	UIC	ΚIE		code	;	
						engr	M.S	MYK		8/1	0/90	 			size	dwg	no					_	-
						chr	M.S	MYK		8/1	0/90	scale		١, ١	al 69155						sheet		
						appd	M.S	MYK	WYK 8/10/90		5:1		А	A OSI									
sheet		revision																					
index sheet																							