
## **SPECIFICATION CONTROL DRAWING** 55PC6077 Date Revision THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT 10-09-03 В

This specification sheet forms a part of the latest issue of Raychem Specifiction 55PC.



CONSTRUCTION DETAILS						
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	DIAMETER ( in.)			WEIGHT ( lbs/1000 ft. )	
		LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC6077-26-*	26	.065	.068	.071	3.96	4.17

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level

**INSULATION FLAWS:** Spark Test: 3.0 kV (rms)

Impulse Dielectric Test, 6.0 kV (peak)

## PART NUMBER:

The "\*" in the part number above shall be replaced by a color code designator with a slash separating

the component wire colors.

Colors shown do not necessarily reflect the sequence of

manufacturing.

1/ Example: AWG26, brown, red and orange component wires; 55PC6077-26 -1/2/3

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "AXXX".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL

Page 1 of 1

TITLE

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



Raychem Wire & Cable 501 Oakside Avenue Redwood Citv. CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297