



Datasheet for part number CIR06G2-24-12S-F80

|   |
|---|
| Our Catalog Part Number: CIR06G2-24-12S-F80   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|   |  |
|---|--|
| Product Datasheet                                     |  |
| SERIES  | Connector with Bayonet Coupling  |
| Shell Style   | Straight Plug Connector  |
| Environmental Class                                   | Swivel backshell suitable for heat shrink tubing but includes individual wire sealing grommet  |
| Shell Size  | 24   |
| Contact Arrangement                                   | 24-12  |
| Total Number of contacts                              | 5 contacts   |
| Number of Contacts Size 4                             | 2 contacts size 4  |
| Number of Contacts Size 12                            | 3 contacts size 12   |
| Gender  | Socket   |
| Contact Type  | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                       | Silver   |
| Shell Material  | Aluminium alloy  |
| Shell Plating   | Olive drab chromate over cadmium plating (conductive)  |
| Wire Size Cross Section for Contacts Size 4           | 22 mm <sup>2</sup> or AWG 4  |
| Wire Size Cross Section for Contacts Size 12          | 3 mm <sup>2</sup> or AWG 12  |
| Contact Rating for Contacts Size 4                    | Maximum Current = 135 A<br>Rated and Test Current = 80 A<br>Potential Drop max. 58 mV  |
| Contact Rating for Contacts Size 12                   | Maximum Current = 41 A<br>Rated and Test Current = 23 A<br>Potential Drop max. 63 mV   |
| Shock Resistance                                      | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling  | 2000 couplings minimum   |
| Service Rating Letter                                 | A  |
| Operating Voltage DC                                  | 700 V  |
| Operating Voltage AC                                  | 500 V  |
| Dielectric strength -<br>Minimum Flashover AC RMS     | 2800 V   |
| Dielectric strength -<br>Test Voltage AC RMS (Hi Pot) | 2000 V   |
| Note  | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General   | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |